


6101225PERMISSIBLE VARIATION ON COMMON
TOLERANCE RINGING ON TOLERANCE SPECIFIED
PERMITS TOLERANCEBREAK ALL SHARP
CORNERED EDGES
OTHERWISE SPECIFIEDCOUNTERSINK ALL TAPPED
HOLES 110° ± 0.015" DIA.FINISH OF FINISH SPEC
WITH A.M. ENGR. STG.

MUST BE FREE FROM BURRS -
WASHER FACES MUST BE FLAT
WITHIN .002 AND PARALLEL
WITHIN .002

CADMIUM PLATE

APERTURE CARD
ONLY

STANDARD PART
DUPLICATE TRACING

										MATERIAL C.R. STEEL TO FULL HARD		NAME OF PART		PART NO.		IT. NO.	
		A ₁ WAS 1/4"								NO. REQUIRED PER ASSEMBLY		ELECTRO-MOTIVE DIVISION					
		TOL'S. ADDED - NOTE REV'D								DATE		GENERAL MOTORS CORPORATION					
		DUPLICATE TRACING ADDED								10-19-34		LA GRANGE, ILLINOIS, U.S.A.					
		STD. PT. STAMP ADDED								O.E. PECK		3/8 AIRCRAFT FLAT WASHER					
X-1338		A		REDRAWN - MATL. ADDED		B-2-60		L.P.C.D.		S.W. BOK							
REV. LET.		REVISION		DATE		BY		CHK.		APPROV.		DATE OF PRINT		PART NO.			
FIRST USED ON		16-184												6101225			