


탄성 계수 E (kg/cm ²)	~ 40	2	4
	~ 30	2	3
	~ 10	1.5	1
	< 0.5	1	1
	~ 3150	-	7
	~ 1800	4	5
	~ 800	3	3
	~ 400	2	3
	~ 200	1.5	2
	~ 100	1	1
인장 강도 σ _b (kg/cm ²)	± 0.005	A	B
	CASTING	(±)	(±)
	~ 200	8	14
	~ 150	7	12
	~ 120	6	10
	~ 100	5	8
	~ 80	4	8
	~ 70	3	4
	~ 60	2	3
	~ 50	1	2
인장 강도 σ _t (kg/cm ²)	~ 120	1	2
	~ 100	1	1
	~ 80	1	1
	~ 60	1	1
	~ 50	1	1
	~ 40	1	1
	~ 30	1	1
	~ 20	1	1
	~ 10	1	1
	~ 5	1	1
용접 WELDING (±)	~ 1500	5.0	8.0
	~ 1200	4.0	7.0
	~ 1000	3.0	5.0
	~ 800	2.0	4.0
	~ 700	1.5	3.0
	~ 600	1.0	2.0
	~ 500	0.8	2.0
	~ 400	0.5	1.2
	~ 300	0.3	0.8
	~ 200	0.2	0.5
인장 강도 σ _t (kg/cm ²)	~ 120	0.15	0.3
	~ 80	0.1	0.2
	~ 50	0.1	0.2
	~ 30	0.1	0.2
	~ 10	0.05	0.1
	~ 5	0.02	0.05
	~ 3	0.01	0.02
	~ 1	0.005	0.01
	~ 0.5	0.002	0.005
	~ 0.1	0.0005	0.001
기계 가공 MACHINING (±)			
열처리 용인 범위 GENERAL TOLERANCE			



- NOTE
1. THE INTERFERED PARTS SHALL BE CUT OFF.
 2. THE CONNECTING LING LINE BETWEEN FLOOR COVERINGS SHALL BE COLD WELDED.
 3. THE EDGE OF FLOOR COVERING SHALL BE SEALED WITH THE SEALANT.
 4. THE HOLE SHALL BE CUT OFF ACCORDING TO THE FLOOR BOARD'S DRAWINGS AFTER AN INSTALLATION.
 5. THE PART NO.1,2,3 AND 4 SHALL BE APPROVED BY CUSTOMER.
 6. IF NECESSARY,FLOOR COVERING SHALL BE SEALED BY SEALANT AT CUTTING PART.
 7. THE PART NO.5 SHALL BE DELIVERED BY SUPPLIER OF FLOOR COVERING AND HAVE SUFFICIENT PERFORMANCE AS COVERING'S ADHESIVE

6	CP91003-445	SEALANT	POLYURETHANE	1		SIKAFLEX 221,GRAY	
5	RFP31003EJ-005	ADHESIVE	ASSY	1		AR	
4	RFP31003EJ-004	FLOOR,COVERING	ASSY	1		T2.5X752	
3	RFP31003EJ-003	FLOOR,COVERING	ASSY	1		T2.5X780	
2	RFP31003EJ-002A	FLOOR,COVERING	ASSY	1		T2.5X780	
1	RFP31003EJ-001	FLOOR,COVERING	ASSY	1		T2.5X1200	
품명 NO.	부품 PART NO.	品名 DESCRIPTION		재질 MATERIAL	수량 QTY	중량 W.T	고 REMARKS
승인 APP	JeongYul Lee 2014.10.14	재질 MAT'L ASSY	명칭 TITLE	FLOOR,COVERING FITTING, T CAR (2/2)			
검도 CHK	KeongBong Park 2014.10.14	출장장 G. W	도면 DRG. NO	RFP31003EJ0			Ver. 00 Rev. -A
설계 DGN	HeonUk Lee 2014.10.14	MC MD CT	MS	SCALE 1/25			RSD1402
검도 DRG	HeeSook Jeong 2014.10.14	B B	SIZE A1	SHEET 2 of 2			RFP-
ISO 9001 REF. NO.		HYUNDAI		Rotem			엔-P R J T 관리번호

[illegible]