Reproduction, dissemination or use of this document or its all contents in any form without the prior written permission of TUVASAS, is prohibited. Offenders will be liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or ornamental design registration.



Realize specular to:
Cod. EM20.24.09.30007

R01

TS 12708 Steel Casting			
	<1000	6,0	0,8
	<630	4,0	0,7
	<400	3,0	0,6
	<250	3,0	0,4
	100	2,0	0,3
	40	1,5	0,2
	L mm	Raw	Form
	Nom. Size	Class	

ISO 2768 General Tolerance			
	<4000	2,0	0,4
	<2000	1,2	0,4
	<1000	0,8	0,3
	<400	0,5	0,3
	30-120	0,3	0,2
	2-30	0,2	0,1
	L mm	m ±	K ±
	Nom. Size	Class	

ISO 13920 Welded Construction			
	>20000	9,0	8,0
	<20000	8,0	7,0
	<16000	7,0	6,0
	<12000	6,0	5,0
	<8000	5,0	4,0
	<4000	4,0	3,0
	<2000	3,0	2,0
	<1000	2,0	1,5
	<400	1,0	1,0
	30-120	1,0	0,5
	2-30	1,0	0,5
	L mm	A ±	E ±
	Nom. Size	Class	

Technical Specifications	-				
Technical Document	-				
Fixture/Mould Asset ID.	-				
Coating/Heat Tre./Roughness	-	1	CHANGED MATERIAL	20/11/2019	D.CARLINO
Paint/Color	-	Modf.No	Modification Description	Date	Sign

No	Parça Adý Designation Name of Item	Adet Qty.	Resim No / Norm Drawing No / Norm	Malzeme Material	Ölçü Dimension	Ağirlik Weight (Kg)
				GE360 (DIN EN10293-2015)		22.7

ISO 1302 ISO 8015 EN 22553				General Tol.	ISO 2768	f ☐	m ☒	H ☐	K ☒
EN 15085-2 Certification Level	CL1 ☐	CL2 ☐		Weld Prod.	ISO 13920	A ☒	B ☐	E ☒	F ☐
	CL3 ☐	CL4 ☐		Cast Steel	ISO 12708	Lm2 ☐	Lr2 ☐	Sm2 ☐	Sr2 ☐
Approved	P.Farina			Scale					
Checked	M.Borlo			1:5					
Prepared	Marco Eid								
TYP	Anti-yaw support LH								
Date:20/07/2018				Sheet:1/1	Size:A3	Rev:01			

TÜVASAS
Turkish Wagon Industry

EM20.24.09.30008