

鋼材の引張強さ (N/mm ²)	40	2	4
	30	2	3
	10	1	1.5
	3	0.5	1
	2150	-	7
	1600	4	5
	800	3	4
	400	2	3
	200	1.5	2
	100	1	1.5
50	-	-	
鋼材の引張強さ (N/mm ²)			
CASTING			
20M	8	14	24
15M	7	12	21
12M	6	10	18
8M	5	8	14
4M	4	6	11
2M	3	4	8
1M	2	3	6
315	1	2	4
120	1	2	3
30	1	1	1
鋼材の引張強さ (N/mm ²)			
WELDING			
20M	-	6.0	8.0
15M	-	5.0	7.0
12M	-	3.0	5.0
8M	0.8	2.0	4.0
4M	0.5	1.2	3.0
1M	0.3	0.8	2.0
315	0.2	0.5	1.2
120	0.15	0.3	0.8
30	0.1	0.2	0.5
3-6	0.05	0.1	0.2
鋼材の引張強さ (N/mm ²)			
MCOSINING			
鋼材の引張強さ (N/mm ²)			
GENERAL TOLERANCE			

2	R50609-1005	SCREW, O.H	SUS304	16	M4X20	
1	RFP65007A0	HAND_RAIL	ASSY	4		
품 NO.	부품 PART NO.	품 DESCRIPTION	재 질 MATERIAL	수량 Q'TY	종류 V.T	비 고 REMARKS
순인 APP	H.G.RYU 2009.03.10	재질 MAT'L ASSY	INSTALLATION, HAND_RAIL (DM)			
검도 CHK	H.S.KIM 2009.03.10	종류 G.W				
설계 DGN	Y.D.KIM 2009.03.09	도면 DRG. NO	MS	RFP65006A0		Ver. 00 Rev. --
제도 DRG	S.W.LEE 2009.03.09	SIZE A1	SCALE 1/4	SHEET 1 of 1		305101 RFP- 반-PRJT 질문
<div style="display: flex; justify-content: space-between; align-items: center;"> <div> 52% REF. NO. </div> <div> HYUNDAI Rotem 현대로템주식회사 </div> </div>						