

적용 규격
SPECIFICATION APPLIED

CLAMP ASSY PART NO.	DESIG -NATION	PIPE DIAMETER	① CLAMP									② BOLT, HEX	③ NUT, HEX	④ WASHER, HEX	⑤ RUBBER, BLACK
			PART NO.	DIMENSION											
				R	L	L1	H	H1	W	t	d				
RMC50012AN0-400	6	6	RMC50012AN0-001	3	15	10	4	1	20	2	6.6	RS60101-058B(M6X20)	RS60401-007B(M6)	RS60801-006B(M6)	RMC50012AN0-012
RMC50012AN0-401	8	8	RMC50012AN0-002	4	15	10	4	1	20	2	6.6	RS60101-058B(M6X20)	RS60401-007B(M6)	RS60801-006B(M6)	RMC50012AN0-013
RMC50012AN0-402	10	10	RMC50012AN0-003	5	15	10	4	1	20	2	6.6	RS60101-058B(M6X20)	RS60401-007B(M6)	RS60801-006B(M6)	RMC50012AN0-014
RMC50012AN0-403	12	12	RMC50012AN0-004	6	18	10	4	2	20	2	6.6	RS60101-058B(M6X20)	RS60401-007B(M6)	RS60801-006B(M6)	RMC50012AN0-015
RMC50012AN0-404	15	15	RMC50012AN0-005	7.5	20	10	4	2	20	2	6.6	RS60101-058B(M6X20)	RS60401-007B(M6)	RS60801-006B(M6)	RMC50012AN0-016
RMC50012AN0-405	20	20	RMC50012AN0-006	10	28	16	5	3	20	2	6.6	RS60101-058B(M6X20)	RS60401-007B(M6)	RS60801-006B(M6)	RMC50012AN0-017
RMC50012AN0-406	25	25	RMC50012AN0-007	12.5	32	16	5	5	20	2	6.6	RS60101-058B(M6X20)	RS60401-007B(M6)	RS60801-006B(M6)	RMC50012AN0-018
RMC50012AN0-407	30	30	RMC50012AN0-008	15	35	16	5	5	20	2	6.6	RS60101-058B(M6X20)	RS60401-007B(M6)	RS60801-006B(M6)	RMC50012AN0-019
RMC50012AN0-408	40	40	RMC50012AN0-009	20	40	16	5	5	20	2	6.6	RS60101-058B(M6X20)	RS60401-007B(M6)	RS60801-006B(M6)	RMC50012AN0-020
RMC50012AN0-409	60	60	RMC50012AN0-010	30	60	24	12	12	38	4	15	RS60101-118B(M12X35)	RS60401-010B(M12)	RS60801-009B(M12)	RMC50012AN0-021
RMC50012AN0-410	70	70	RMC50012AN0-011	35	70	27	12	12	50	6	19	RS60101-157B(M16X40)	RS60401-011B(M16)	RS60801-010B(M16)	RMC50012AN0-022

두께
THICKNESS

길이
LENGTH

높이
HEIGHT

등급
GRADE

주입
CASTING

용접
WELDING

기계
MACHINING

~ 40

~ 30

~ 10

< 3

~ 3150

~ 1600

~ 800

~ 400

~ 200

~ 100

A

B

(±)

~ 20M

~ 15M

~ 12M

~ 8M

~ 4M

~ 2M

~ 1M

~ 315

~ 120

~ 30

A

B

C

(±)

~ 20M

~ 15M

~ 12M

~ 8M

~ 4M

~ 2M

~ 1M

~ 315

~ 120

~ 30

3~6

A

B

C

(±)

KA 6

Ød DRILL HOLE

5

1

2

3

4

H1

L

L1

H

H1

W

t

d

A

CLAMP, K-A TYPE

RMC50012AN0

HYUNDAI Rotem 현대로템주식회사

5

4

3

2

1

품번
NO.

부품 번호
PART NO.

품명
DESCRIPTION

재질
MATERIAL

수량
Q'TY

중량
W.T

비고
REMARKS

승인
APP

검도
CHK

설계
DGN

제도
DRG

참고번호
REF. NO.

소재
MAT'L

중량
G.W

일 반 공 차
MC WD CT

도면 번호
DRG. NO

MS

SCALE

N/S

매수
SHEET

1

of

1

CLAMP, K-A TYPE

RMC50012AN0

Ver. 00

Rev. --

3D5101

MC-

년-PRJT

정리번호

기호
MARK

일자
DATE

변경 내역
DETAIL OF REVISION(E.C ZONE)

설번번호
E.C NO.

설계
DGN

검도
CHK

승인
APP

적용 규격
SPECIFICATION APPLIED

기호
MARK

일자
DATE

변경 내역
DETAIL OF REVISION(E.C ZONE)

설번번호
E.C NO.

설계
DGN

검도
CHK

승인
APP

NOTE.

1. THE LENGTH OF USED BOLTS IS CALCULATED ON Max. 4.5mm OF CLAMP BRACKET'S THICKNESS AND THE LENGTH OF NUT/SPRING WASHER)

2. MARK ON CLAMP'S SURFACE [A] AS ILLUSTATION, USING OIL PAINT.

본 도면은 당사 재산으로서 허가없이 무단복사/배포 금지함 . PROPERTY OF ISSUING ENTITY. CANNOT BE DISTRIBUTED OR REPRODUCED WITHOUT AUTHORIZATION.

CAT1A